









SOFAR 30k~40kTL

30000/ 33000/ 36000/ 40000



Three-Phase Dual-MPPT

-  Super large 4-inch LCD
-  Fuse free design
-  Outdoor IP65 protection level
-  I-V curve scanning function
-  Max. efficiency up to 98.7%
-  Support Modbus communication, external Wifi/ Ethernet/ GPRS (optional)

Datasheet	SOFAR 30000TL	SOFAR 33000TL	SOFAR* 36000TL	SOFAR 40000TL
Input (DC)				
Recommended Max. PV input power	39900Wp	43890Wp	47880Wp	53200Wp
Max DC power for single MPPT	15360W	17000W	20400W	20400W
Number of MPPT trackers	2			
Number for DC inputs	4 for each MPPT			
Max. input voltage	1000V			
Start-up voltage	350V			
Rated input voltage	600V	600V	600V	700V
MPPT operating voltage range	250V-960V			
Full power MPPT voltage range	480V-800V	480V-800V	500V-800V	560V-800V
Max. input MPPT current	32A/32A	35A/35A	38A/38A	35A/35A
Max. input current per string	12A			
Maximum DC input short circuit current per MPPT	40A	40A	42A	40A
Output (AC)				
Rated power	30000W	33000W	36000W	40000W
Max. AC power	30000VA	33000VA	36000VA	40000VA
Max. Output current	43A	48A	54A	48A
Nominal grid voltage	3/N/PE, 220/380Vac, 230/400Vac, 240/415Vac			3/N/PE or 3/PE, 277/480Vac
Grid voltage range	310Vac-480Vac (According to local standard)			422Vac-528Vac(According to local standard)
Nominal frequency	50/60Hz			
Grid Frequency range	45Hz-55Hz/54Hz-66Hz (According to local standard)			
Active power adjustable range	0-100%			
THDi	< 3%			
Power factor	> 0.99 (adjustable +/- 0.8)			
Performance				
Max efficiency	98.5%	98.5%	98.5%	98.7%
European weighted efficiency	98.2%	98.2%	98.2%	98.4%
Self-consumption at night	< 1W			
MPPT efficiency	> 99.9%			
Protection				
DC reverse polarity protection	Yes			
DC switch	Yes			
Protection class/ overvoltage category	I/III			
Safety protection	Anti islanding, RCMU, Ground fault monitoring			
ARPC	Anti reverse power controller (optional)			
Input/output SPD (II)	Optional			
Communication				
Power management unit	According to certification and request			
Standard communication mode	RS485, Wifi/Ethernet/GPRS (optional), SD card, Multi-function relay			
Operation data storage	25 years			
General Data				
Ambient temperature range	-25°C ~ +60°C			
Topology	Transformerless			
Degree of protection	IP65			
Allowable relative humidity range	0-100%			
Max. operating altitude	2000m			
Noise	< 30dB	< 45dB	< 45dB	< 45dB
Weight	50kg			
Cooling	Natural	Fan	Fan	Fan
Dimension	774*564*298mm			
Display	LCD display			
Warranty	5 years/ 7 years/ 10 years			
Standard				
EMC	EN 61000-6-2, EN 61000-6-4			
Safety standards	IEC62109-1/2, IEC62116, IEC61727, IEC-61683, IEC60068(1,2,14,30)			
Grid standards	AS/NZS 4777, AS/NZS 61000, VDE V 0124-100, V 0126-1-1, VDE-AR-N 4105, CEI 0-21/CEI 0-16, EN50549, G59, Rd1699, UTE C15-712-1, EN50530			

The models marked with "*" should be available only for some designated countries.